

EASY ROLLER® GDO-6v4

ROLLER DOOR OPENER



Simple, compact and slimline roller door opener.

The EasyRoller® builds on decades of innovation to deliver a slim, reliable and secure roller door opener. Suitable for all residential roller door applications, it is compatible with Automatic Technology's Smart Phone Control Kit and Wireless Safety Beams.

Featuring a strong 600N DC motor, EasyRoller® is designed to reliably lift and lower roller doors. The opener comes with TrioCode™128 Remote Controls, a bright LED courtesy light for convenience and features soft start-and-stop functionality.

WHAT'S INCLUDED:



Opener with LED Courtesy Lights



2x TrioCode™128 transmitters



Wireless Wall Button

AT A GLANCE:

SECURE & RELIABLE TRANSMITTERS

The TrioCode™128 remote control ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol for the ultimate in security.



POWERFUL MOTOR

This EasyRoller® 600N DC motor reliably operates doors up to 110kg[^]

LED COURTESY LIGHT

A Courtesy Light means your immediate surrounds can be lit to provide security and convenience, and being an LED light source you know it's going to last.

7 YEAR WARRANTY

The Series 2 EasyRoller® is backed by a 7-year/20,000 cycle warranty*, giving peace of mind.

[^]When maximum spring balanced weight is 20kg.

*Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under the Australian Consumer Law.

TECHNICAL SPECIFICATIONS



EASY ROLLER® GDO-6v4

Power	Input Voltage	230-240V a.c. 50Hz
	Transformer Rating	100VA
	Standby Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
Door Sizes	Maximum Door Weight	110kg [†]
	Rated Door Area	16.5m ²
	Typical Travel Speed	130mm/sec
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	TrioCode™ 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Capacity (x 4-button registers)	64
Additional Features	Courtesy Light	2 x LED
	Safety Beam Compatibility	2 x Wireless Safety Beams or 2-Wire Safety Beams
Network Compatible	Ready for Smart Phone Control Kit	
Warranty*	7 years/20,000 cycles	

SAFETY & SECURITY FEATURES

- Soft Start/Soft Stop
- Intelligent Safety System
- Door Profiling
- TrioCode™128


POWER & MOUNTING SYSTEM

- DC Motor – 600N
- Slim Fit

OPERATING MODES

- Wireless Safety Beam
- Service Indicator
- LED Courtesy Lights
- Ventilation Mode
- Time Clock
- Auto Close
- Vacation Mode
- AUX Auxiliary Output

OPTIONS AND UPGRADES



SMART PHONE CONTROL KIT

Monitor and operate your garage door and gate on your smart phone from anywhere[‡]. Control multiple locations from the one app, such as home and holiday home. Receive push notifications about the status of your garage door and gate, view past activities, set various opening modes, customise user settings and more in the Automatic Technology App.



BATTERY BACK UP

In the event of power failure, your door will still operate.



WIRELESS SAFETY BEAMS

Protect your family and possessions by detecting obstructions while your door is closing.



SMARTSOLAR™ READY

Using only one solar panel the sun does all the work for you.

For more product information, visit www.automatictechnology.com/au

* For full terms and conditions of our warranty, please go to www.automatictechnology.com/au. Our warranty is in addition to any consumer guarantees that may apply under the Australian Consumer Law. © 2025 Automatic Technology (Australia) Pty Ltd. All rights reserved. The Automatic Technology logos, TrioCode & EasyRoller are registered trademarks. In an ongoing commitment to product quality, the specifications may change from time to time. Date: August 2025. Automatic Technology (Australia) Pty Ltd ABN 11 007 125 368, www.automatictechnology.com/au, 1300 133 944.



automatic
TECHNOLOGY®