# TECHNICAL DATA SHEET

## HHS 2000 adhesive lubricant

**Art. no. 0893 106**
P. Qty.: 1 / 6 / 12 / 24




**The extremely high-pressure-resistant, partially synthetic oil offers excellent adhesion properties with outstanding corrosion protection**

- Resistant to high pressures
- Extraordinarily tear-proof lubricating film with excellent noise and vibration dampening
- Creeping properties
- Excellent lubricating properties
- Reliable protection against corrosion.
- Lubricant is not flung off turning and rotating parts
- Good material compatibility
- O and X-ring compatible, also compatible with plastics
- Neutral effect on painted surfaces
- Resistant to spray water and salt water, weak acids and alkalis

| | |
|---|---|
| Chemical basis | Hydrocarbon |
| Oil basis | Synthetic mineral oil |
| Colour | Yellowish |
| Smell/fragrance | Oil |
| Density | 0.742 g/cm³ |
| Density conditions | at 20°C |
| Min. temperature conditions | -25 °C |
| Max. temperature conditions | 180 °C |
| Max. temperature resistance | 200 °C |
| Min. flashing point of active ingredient | 300 °C |
| Kinematic oil basis viscosity | 1500 cSt |
| Silicone-free | Yes |
| Acid-free | Yes |
| Resin-free | Yes |
| AOX-free | Yes |
| Resistance against | Salt water, Weak lyes, Weak acids, Splash |
| Contents | 500 ml |
| Container | Can |
| Weight of content | 315 g |
| Shelf life from production | 24 Month |

PR01_0893106, TDB, Rev: 0.781, State: 08. 07. 2026

# TECHNICAL DATA SHEET

## Application area

For professional use for universal lubrication and for high pressure loads, e.g. shifting, accelerator and clutch linkages, Bowden cables, bolts, joints, hinges, reversing levers, lock strikers, drag link ends, sliding rails, sprockets, toothed racks, open gears etc.

## Application information

First, clean and degrease parts to be lubricated with HHS Clean art. no. 0893 106 10. Shake the can before use, spray the parts and let it take effect briefly. After using, spray the can upside down until it is empty.
Resistant to high pressure loads, the HHS 2000 lubricating film remains active and does not strip off despite the high pressure load and shearing motion of the base body. Reliably separates the counterpart body from the basic body and thus ensures optimum wear protection at higher pressure loads.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.

PR01_0893106, TDB, Rev: 0.781, State: 08. 07. 2026

Adolf Würth GmbH & Co. KG, 74650 Künzelsau